

*Truly,
McKenna*

Just Add Stitches!

Beach Walk



Large Two-Sided Throw Pillow

20" x 18"

Designed by Michelle Pratt,
Exclusively for McKenna Ryan

Materials Needed:

- Beach Walk Truly McKenna Art Print Panel: To the Point / Holiday for Two (BW02/01-P)
- Fabric 1: AYC-16317-59 Ocean - ½ yard for backing & binding for back
- Fabric 2: AYC-16315-333 Sea Glass - Fat Quarter for edge piping & HST
- Fabric 3: AYC-16318-59 Ocean - Fat Eighth for HST
- 1 yard fusible fleece
- Muslin for backing
- 20" x 20" Pillow insert

Before Getting Started:

- Use ¼" seam allowance
- HST – Half Square Triangle
- RST – Right Sides Together
- WOF – Width of Fabric

Cutting:

- You'll need to cut the panel into two separate pieces. To separate the two panels, measure ¾" to the right of the bike's front tire and cut vertically.
 - Trim the *To the Point* panel (bike) to 11½" x 18½" for the back of the pillow.
 - Be sure to trim on the remaining 3 sides, keeping the image centered while maintaining the ¾" on the right side of the panel.
 - Trim the *Holiday for Two* panel (chairs) to 20½" x 18½" for the front of the pillow.
 - Be sure to trim on the remaining 3 sides only, keeping the image centered.
- Fabric 1
 - Cut one - 1½" x WOF strip, set aside for binding pillow back pieces
 - Cut one - 14" x 18½" piece
 - Line up the scenery on the fabric with the *To the Point* panel. These will become your pillow backing pocket.
- Fabric 2 - Cut four - 1" x 20" fabric strips for piping
- Fabrics 2 and 3 - make 9 - 2½" HST using your preferred method

Front Panel:

1. Fuse fleece to back of the *Holiday for Two* panel. Fusible fleece will allow you to quilt on the panel or do lots of decorative stitching to highlight areas of the scenery without moving or puckering.
2. Iron the four piping strips in half lengthwise.
3. Sew strips to edge of front panel on all four sides, overlapping the corners. Sew close to the edge, matching all raw edges.

Back Panel:

1. Sew the 9 HST in a strip together. See Diagram 1 for arrangement.
2. Sew the HST strip on the **RIGHT** side of the *To the Point* panel.
3. Make a quilt sandwich with the muslin, batting and the *To the Point* panel.
4. Make a cross hatch quilting design on the panel with diagonal lines 2" apart. Trim quilt sandwich to approximately 13" x 18½".

***Hint:** Draw diagonal lines using a Frixion pen and a ruler to create a diamond pattern and simply sew on all the lines.
Iron and the Frixion pen lines will disappear!



5. Repeat above process with the 14" x 18½" Fabric 1 piece. Sandwich, quilt and trim to 13" x 18½".
6. Bind the HTS edge and one 18½" edge of the quilted pillow back panels.
7. Embellish back panels with stitching or small appliques at this time.

Assembly:

1. With RST, layer the pocket flaps with bound edges facing in and overlapping each other with the pillow front. Be sure to layer the HST back panel closest to the pillow front so it's on top when turned right side out.
2. Pin around the edge of pillow and sew a ¼" seam.
3. Sew a zig-zag close to edge to help prevent fraying.
4. Turn pillow cover right side out and insert pillow form.

Diagram 1

